

MSDS Number : 12032  
Version Date : 12/09/2002

Product Name : DURA LIFE HEAT TRANSFER OIL- ALL GRADES  
Product Use : NA  
Synonyms : HT 10/15/22/32/46/68

### **MANUFACTURER**

American HiTech Petroleum & Chemical Inc.  
P.O. Box 657  
ALAMEDA , CA 94501 USA  
Internet Address : [www.amtecol.com](http://www.amtecol.com) Medical Emergency : (866) 268 1888  
Technical Assistance : (510) 208 1888  
Customer Service : (510) 208 1888  
Fax Number : (510) 627 0001

Component CAS No. Weight Percent Range Hazardous in Blend  
- LUBRICATING BASE OILS MIXTURE <95 No  
- ANTIWEAR ADDITIVES, R&O INHIBITORS MIXTURE < 5 No  
- VISCOSITY INDEX IMPROVER MIXTURE < 5 No  
- POUR POINT DEPRESSANT MIXTURE < 1 No  
- ANTIFOAM ADDITIVE MIXTURE < 1 No

*This product is NOT HAZARDOUS according to OSHA 29 CFR 1910.1200.*

### **IMMEDIATE HEALTH EFFECTS**

EYE: Not expected to cause prolonged or significant eye irritation .

SKIN: Contact with the skin is not expected to cause prolonged or significant irritation.  
Not expected to be harmful to internal organs if absorbed through the skin .

INGESTION: Not expected to be harmful if swallowed .

INHALATION: This product is not expected to pose an inhalation hazard under conditions of normal use or foreseeable misuse. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. Acute and chronic overexposures generated under unusual conditions may be irritating to the respiratory tract .

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and seek immediate medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If

material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately .

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If vapor or mist is generated when the material is heated, and the victim experiences signs of respiratory tract irritation, remove to fresh air .

Ingestion: No treatment is necessary under ordinary circumstances. Do not induce vomiting. This material does not present any known ingestion hazard .

### **Flammable Properties**

Flash Point : > 270oF, >132oC

Test Method : ASTM D 92 (C.O.C.)

Flammable Limits in Air

Upper Percent : NA

Lower Percent : NA

Autoignition Temperature : NA

Test Method : NA

NFPA Classification : Class III-B combustible liquid

Extinguishing Media : Use dry chemical, foam, or carbon dioxide .

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment : Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid .

Unusual Fire and Explosion Conditions : Dense smoke may be generated while burning. Carbon

monoxide, carbon dioxide, and other oxides may be generated as products of combustion .

Hazardous Combustion By-Products : None

## **Emergency Number : 866-268-1888**

Accidental Release Measures : Stop the source of the leak or release. Clean up releases as soon as possible, observing precautions in Exposure Controls/Personal Protection. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate , remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases .

Handling : Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106 - Flammable and Combustible Liquids .

Storage : Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials. See also additional information section below .

Empty Container Warnings

Drums : Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed. Empty containers retain product residue and can be dangerous .

Plastic : Do not reuse this container. Empty container may retain product residues .

Exposure Limits and Guidelines : This product does not contain any components with OSHA or ACGIH exposure limits .

Personal Protective Equipment

Eye/Face Protection : No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as good safety practice .

Skin Protection : No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc..) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc..). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated .

Respiratory Protection : Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handle, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres .

Personal Hygiene : Always wash hands and face with soap and water before eating, drinking, or smoking. Consumption of food and beverage should be avoided in work areas where this product is present .

Engineering Control/Work Practices : Use in a well-ventilated area. If user operations generate an oil mist, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended mineral oil mist exposure limits .

Appearance : Bright Yellow Brown Pour Point : <-10oF(-23.3oC)

Odor : Petroleum - mild Solubility in Water : Negligible in water

Physical State : Liquid Vapor Pressure : < 0.1 mm Hg

Boiling Point : > 700 oF (371.1 oC) Vapor Density (air=1) : NA

Melting Point : NA pH : NA

Specific Gravity : < 1 Viscosity @ 100 oC : NA

Chemical Stability : Stable

Condition to Avoid : High heat and open flames

Incompatible Materials to Avoid : May react with strong oxidizing agents

Primary Eye Irritation : NA

Primary Skin Irritation : NA

Acute Dermal Toxicity : NA

Subacute Dermal Toxicity : NA

Dermal Sensitization : NA

Inhalation Toxicity : NA

Oral Toxicity : NA

Mulagenicity : NA

Carcinogenicity : The International Agency for Research on Cancer (IARC) has concluded that there is inadequate data to evaluate the carcinogenicity to experimental

animals of this class of product. IARC has concluded there is sufficient evidence that used gasoline-engine motor oils produce skin tumors in experimental animals. Also, IARC has determined this class of products belongs to Group 3 - "not classifiable as to its carcinogenicity to humans" .

Reproductive and Developmental Toxicity : NA

Teratogenicity : NA

Immunotoxicity : NA

Neurotoxicity : NA

Ecotoxicity : The toxicity of this material to aquatic organisms has not been evaluated. Consequently, this material should be kept out of sewage and drainage systems and all bodies of water .

Environmental Fate : This material is not expected to be readily biodegradable .

Regulatory Information : All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled .

Waste Disposal Methods : Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible .

### **U.S. Department of Transportation (DOT)**

Highway / Rail (Bulk) : Not Regulated

Highway / Rail (Non-Bulk) : Not Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions .

International Information

Vessel : IMDG Not Regulated

Air : ICAO Not Regulated

Regulatory Lists Searched : The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below .

Health & Safety : 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325 .

Environmental : 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depleters, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCOMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA

Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs .

International : 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US - TSCA Section (12)(b) - export notification .

State Lists : 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK,

64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances .

Inventories : 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA, 85 - China Inventory .

Regulatory Search Results : No components appear on any of the regulatory lists searched .

U.S. TSCA Inventory : All components of this material are on the US TSCA Inventory .

SARA Section 313 : This product is not known to contain any SARA, Title III, Section 313 Reportable Chemicals at or greater than 1.0% (0.1% for carcinogens)

IARC : NA

SARA 311 / 312 Categories : Not Regulated

Canadian WHMIS Classification : Not a controlled substance under WHMIS

European Union Classification

Hazard Symbols : No classification recommended

Risk Phrases : No classification recommended

Safety Phrases : No classification recommended

### **Health and Environmental Label Language**

**CAUTION** : Contains Petroleum Lubricant. Repeated skin contact can cause skin disorders .

**ATTENTION** : Used motor oil is a possible skin cancer hazard based on animal data. Repeated exposure to oil mist in excess of the OSHA limit (5mg/m<sup>3</sup>) can result in accumulation of oil droplets in pulmonary tissue .

**PRECAUTIONARY MEASURES** : Avoid excessive & prolonged skin contact. Wash thoroughly after handling. Avoid generation and inhalation of oil mists .

**INSTRUCTIONS IN CASE OF FIRE OR SPILL** : In case of fire, use water spray, foam, dry chemical or carbon dioxide. Water spray may be ineffective, but can be used to cool containers. In case of spill, do not use water, soak up with absorbent material .

**DON'T POLLUTE, CONSERVE RESOURCES, RETURN USED OIL TO COLLECTION CENTER .**

Prepared by : American HiTech Petroleum & Chemicals Inc.

P.O. Box 657

ALAMEDA , CA 94501 USA

**Disclaimer of Warranty** : The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose .