MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION							
NFPA Rating: Health-2; Flammability-1; Reactivity-1; Special-0 HMIS Rating: Health-2; Flammability-1; Reactivity-1; Personal Protection-B							
	DOT Hazard Classification: ORM-D						
Address: 3908 3rd Avenue South	Identity (trade name as used on label):						
Address: Birmingham, AL 35222	MISTY OVEN AND GRILL CLEANER						
	MSI	OS Number: IT20A	Rev	ision- 9			
Information Calls: (205)592-0844 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ISOBUTANE/PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
SODIUM HYDROXIDE		1310-73-2	No	2mg/M3	2mg/M3	d	
POTASSIUM HYDROXIDE		1310-58-3	No	2mg/M3	2mg/M3	d	
HEXYLENE GLYCOL		107-41-5	No	N/E	25	е	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Soiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 1.060							
	Evaporation Rate (BuAc = 1): Slower						
Solubility in Water: Soluble Water Reactive: No							
Appearance and Odor: Tan foamy gel with lemon fragrance.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA LAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:							
(aerosols) NON-FLAMMABLE FLASH POINT AND METHOD USED (non-aerosols): N/A	N/E % LEL: N/E % UEL: N/E EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.						
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong acids and oxidizers. Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible							
unconsciousness.							
Eye Contact: CAUSTIC: May cause burns. Skin Contact: CAUSTIC: May cause burns.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. CAUSTIC: May cause burns.							
CHRONIC EFFECTS: Lab animals have experienced anemia, liver, kidney, lung, blood damage to Hexylene Glycol. (Effects due to excessive							
exposure to the raw materials of this mixture) May cause burns, dermatitis, respiratory illness, nystagmus and central nervous disorders.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water or milk. Get immediate medical attention. SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or							
Federal regulations. Dilute with water, absorb with cloth or neutralize with dilute acid and flush to sewer.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Do not use on aluminum. Avoid breathing vapors							
Avoid breathing vapors. We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any							

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF May 08, 2003. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.