MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION

NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special-0	**HMIS Rating:** Health-2; Flammability-3; Reactivity-0; Personal Protection-B
Distributor's Name: K-Chem, Inc, Address: 3908 3rd Avenue South Birmingham, AL 35222	**DOT Hazard Classification:** ORM-D **Identity** (trade name as used on label)**:** **FIRE ANT INJECTOR SPRAY**
Date Prepared: 03/26/96 Prepared By: LF	**MSDS Number:** IS20 Revision- 6
Information Calls: (205)592-0844 **EMERGENCY RESPONSE NUMBER: 1(800)255-3924**	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATES	8052-41-3	No	500	100	d
PERCHLOROETHYLENE	127-18-4	Yes	25	25	a,b
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	**Specific Gravity** (H2O=1): Concentrate Only = 0.993
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	**Vapor Pressure** (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	**Evaporation Rate** (= 1): N/E
Solubility in Water: Insoluble	**Water Reactive:** No

Appearance and Odor: Light straw color with light chlorinated solvent odor.

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) **EXTREMELY FLAMMABLE**	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E

FLASH POINT AND METHOD USED (non-aerosols): N/A **SPECIAL FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus.	**EXTINGUISHER MEDIA:** Foam, dry chemical, carbon dioxide.

Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [X] STABLE [ ] UNSTABLE	**HAZARDOUS POLYMERIZATION** [ ] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Reactive metals, aluminum, magnesium, potassium, sodium, strong oxidizers, alkalis.	**Conditions to Avoid:** Open flame, welding arcs, heat, sparks.

Hazardous Decomposition Products: CO, CO2

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: [X] INHALATION [ ] INGESTION [ ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS

ACUTE EFFECTS

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

Eye Contact: Irritation.	**Skin Contact:** Possible mild irritation due to defatting of skin.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormalities, cental nervous system depression, lung, kidney and liver damage.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.

Skin Contact: Wash with soap and water. If irritated, seek medical attention.

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.

Protective Gloves: Neoprene gloves recommended.	**Eye Protection:** Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.Remove ignition sources.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only