K-Chem, Inc.

TECHNICAL DATA SHEET

Product Name: Solv-300
Item Number: SO112

Description: Solv 300 is a very low odor solvent degreaser that is excellent for removing most greases, oils, lubricants, etc. It is safe on plastic, has a high flash point, and leaves no residue. It has low odor and low inhalation toxicity for maximum work comfort and safety. Non-conductive, high flash point, leaves no residue. Safe on ferrous and non-ferrous metals, and on many types of plastics, such as polyethylene, polypropylene, PETE, PVC and electrical wiring, may be substituted for chlorinated solvents in applications below.

Directions:

Cold Degreasing- May be used for immersion cleaning in non-agitated vats, circulation-type units, ultrasonic, air-agitated and pressure-spray units. Soak until clean. If desired, remove parts from vat and spray fresh product to flush away dissolved soils. Let product evaporate, or blow dry with air.

Electrical Contact Cleaning- May be used to clean electrical and electronic parts and equipment. Safe on electrical wiring. De-energize equipment first and blow dry with air before turning back on. Do not spray on hot surfaces. Do not use on operating equipment that may spark or that has an open flame.

WARNING: COMBUSTIBLE MIXTURE. It is recommend that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Apply this product only as specified on this label. KEEP OUT OF REACH OF CHILDREN. Refer to MSDS for additional safety information.

Spill Or Leakage Procedures: Contain spill. Do not contaminate sewers, ground or surface waters. Soak up in inert absorbent. Place in properly labeled, sealed, non-leaking containers for proper disposal.

Product Specifications:

Odor:	Slight Petroleum Distillate
Appearance:	Clear Colorless Liquid
Flash Point:	143°F
Evaporation Rate:	0.06
USDA:	K-2
KB Value:	33
Dielectric Breakdown Voltage:	29,600 volts

CAS NUMBERS: Aliphatic Hydrocarbon 64742-47-8
HMIS RATING: Health-2; Flammability-2; Reactivity-0; Personal Protection-G.

06/02

K-Chem, Inc.
P.O. Box 530632 • Birmingham, AL 35253-0632
205-592-0844 • Fax: 205-592-8106